

CONTACT INFORMATION

PREPARER INFORMATION

AAG PROJECT NUMBER: AAG21-092

CONTACT: CURTIS D. CUSHMAN

ADDRESS: 8947 BUTTONWOOD LANE NE
OLYMPIA, WASHINGTON 98516

TELEPHONE: (360) 491-5155

CELL: (360) 481-6677

EMAIL ADDRESS: CURTIS.CUSHMAN@COMCAST.NET

CLIENT INFORMATION

CLIENT: FULLER DESIGN

TELEPHONE: (360) 880-4927

BILLING ADDRESS: 1101 KRESKY VENUE
CHEHALIS, WASHINGTON 98531

SITE ADDRESS: 0 JACKSON ROAD
CHEHALIS, WASHINGTON
SECTION 03 TOWNSHIP 13N RANGE 02W PT LT 8 SE RD BLK 1
RICHARDT'S RPLT BLK 4-6 PARCVIA ADD PRCL B BL-09-148
335384

PARCEL: 010799001000

GPS LOCATION: 46.641138 -122.926586 (DD)

ALL AMERICAN GEOTECHNICAL, INC.

TABLE OF CONTENTS

CONTACT INFORMATION	1
TABLE OF CONTENTS	2
SITE VISIT AND EVALUATION	3
SITE	3
SITE GEOLOGY	4
SITE HYDROLOGY	5
SITE SOILS	5
SITE VEGETATION	6
PITTING	6
SITE WORK	7
CONCLUSIONS	8
REPORT LIMITATIONS AND GUIDELINES FOR USE	9
READ THESE PROVISIONS CLOSELY	9
REPORT LIMITATIONS AND GUIDELINES FOR USE	9
READ THESE PROVISIONS CLOSELY	9
REFERENCES	11
SAMPLING LOCATIONS	13
LABORATORY RESULTS	14
SIEVE REPORT -- PIT 1 @ 6-FT BGS	14
SIEVE REPORT -- PIT 1 @ 8-FT BGS	15
HYDROMETER REPORT -- PIT 1 @ 8-FT BGS	16
ASTM D4318- LIQUID LIMIT, PLASTIC LIMIT, & PLASTICITY INDEX OF SOILS -- PIT 1 @ 8-FT BGS	17
SIEVE REPORT -- PIT 2 @ 6-FT BGS	18
HYDROMETER REPORT -- PIT 2 @ 6-FT BGS	19
ASTM D4318- LIQUID LIMIT, PLASTIC LIMIT, & PLASTICITY INDEX OF SOILS -- PIT 2 @ 6-FT BGS	20

ALL AMERICAN GEOTECHNICAL, INC.

SITE VISIT AND EVALUATION

**FULLER DESIGNS
645 SE PROSPECT STREET
CHEHALIS, WA 98532**

**RE: JACKSON VILLAS LANDSLIDE HAZARD SITE VISIT
0 JACKSON ROAD CHEHALIS, WASHINGTON
SECTION 03 TOWNSHIP 13N RANGE 02W PT LT 8 SE RD BLK
1 RICHARDT'S RPLT BLK 4-6 PARCVIA ADD PRCL B BL-09-
148 335384
PARCEL: 010799001000
AUGUST 14, 2021**

Dear Fuller Designs:

This report is a follow-up to the initial site visit report of November 24, 2020. All American Geotechnical, Inc (AAG) was commissioned by Fuller Designs (client) in November, 2020, to do a site visit to determine the geology and landslide potential for the above parcel. This is in reference to a proposed development of multiple family dwellings on the parcel. The site visit was done by Curtis D Cushman, L.G., L.E.G., on November 13, 2020. The client representative was not on site. The day was rainy.

A pitting program to determine the nature of underlying soils and landslide deposits in select locations was undertaken on July 13, 2021. The day was sunny and Curtis D Cushman L.E.G. and Blaise Jelinek E.I.T. both of AAG were on site. Excavation was done by Jason Alvis in a SANY S4650C backhoe excavator. The client representative, Aaron Fuller, was on site at the end of the pitting program. The program will be described below.

This report supersedes that of November, 2020 and any earlier report from 2021. The purpose of this report is to incorporate sub-surface pitting information into the site evaluation. This was at the request of the client and was done following the original report of November 2020.

SITE

The parcel is an imperfect rectangle, long to the northeast-southwest. A square section of the southernmost corner is omitted from the rectangle as it is not part of the parcel. This forms a blunt panhandle on the parcel's southwestern side which faces Jackson Highway. The northwest side is along Kennicott Road and the northeast side is along Hosanna Lane. The parcel looks like Nebraska.

The parcel slopes down to the southwest with the steepest area near the center of approximately 16%. The edges of the roads commonly drop off steeply near the parcels southern end, less so to the north. The lower land is locally designated wetlands.

ALL AMERICAN GEOTECHNICAL, INC.

Site observation indicated various lithologies, dominantly silt with sand, and rare gravel present locally. According to the client, the area of material lining Hosanna Lane contains fill to a depth of 10 feet at least, including rubble, organic refuse, and blocks of concrete.

At the time of the pitting program, much of the upper part of the parcel had been scraped revealing the soil underneath. The initial site description was validated by the pitting program including the presence of fill which includes concrete and old pipes, fill soil, some rebar, etc.

SITE GEOLOGY

The parcel is overall mapped (Lewis County GIS and confirmed on the Centralia 100:000 Quadrangle) as being a “mass wasting deposit(s), mostly landslide” (**Qls**). This is a general description and is not site-specific. These deposits are common in the Centralia-Chehalis region where they are commonly associated with erosion and mass wasting of the **Qlh** Logan Hill Formation sediments at the end of the last glacial epoch.

Allen Fiksdal, in *Slope Stability of the Centralia-Chehalis Area Lewis County, Washington* (OF Report 78-2, 1978), mapped these features as **Ols** - Old Landslides. He wrote: “...these areas are not generally observed to be unstable, but because of the nature of subsurface materials, low density development is recommended. Engineering studies should be required if natural slopes are over 30 percent.” No such slopes were observed.

Site observation indicated various lithologies, dominantly sand and silt with minor gravel present as well. According to the client, the area of soil lining Hosanna Lane contains fill to a depth of 10 feet at least, including rubble, organic refuse, and concrete. This fill blankets much of the upper part of the parcel but to a lesser amount than at the northern property line. A “wedge” of fill, diminishing to the south, is inferred from this and appears to be confirmed in site observations and pitting.

Along this area and looking into the higher banks of material (as along Kennecott Road and Hosanna Lane) and the overall surface, there was no evidence of faulting, failure, or cracking on a large scale. There is abundant vegetation locally, mainly to the south, so some features may be obscure. *However, overall, there is no evidence of movement or downslope displacement.*

Liquefaction is **Low to Moderate**, and the site class is **D** which is **Stiff Soil**. Please see References, below.

The classification of the soil is based on the Washington DNR Site Class Map for Lewis County Washington. It is mapped as site class D. The DNR maps contain the following wording:

Because the data used in producing this site class map is based on regional geologic mapping, this map cannot be used to make a final determination at any specific locality. This determination requires a site-specific evaluation performed by a qualified practitioner.

In pitting, we found there to be silts on top of elastic silts. There is possibly some clay content in the latter, but Site Class E is specifically “Soft Clay Soil” and does not apply as this material is silt. A major difference in the two, despite some similarities, is that clays are chemically altered minerals with

ALL AMERICAN GEOTECHNICAL, INC.

characteristics different from silts. Clays are plastic, and silts are elastic. The difference is that silts do not change volume when under pressure whereas clays plastically deform and swell when hydrated.

The definition for Groups A to E in ASCE 7 is based on the top 100 feet of “soil and rock” measured below the base of the building. It is for this reason that soil types and underlying geology are commonly “lumped” into one classification or the other. At least one source (TSIB) considers Class D as “default.” So design for the overall structure should follow design criteria for class D with the understanding that clay may be present, but, according to the lab analysis, it would be minor.

SITE HYDROLOGY

There was no ponding seen on the upper part of the property during the rain at the time of the first visit, but light sheet water flow was entering the parcel from the slope descending from Hosanna Lane. There is a wetlands delineated in the center of the property.

SITE SOILS

The USDA WSS maps most of the site as *Galvin silt loam, 0 to 8 percent slopes*.

89—Galvin silt loam, 0 to 8 percent slopes

Map Unit Setting

- *National map unit symbol:* 2hht
- *Elevation:* 100 to 1,770 feet
- *Mean annual precipitation:* 40 to 70 inches
- *Mean annual air temperature:* 52 degrees F
- *Frost-free period:* 150 to 200 days

Map Unit Composition

- *Galvin and similar soils:* 85 percent
- *Minor components:* 15 percent

Description of Galvin

Setting

- *Landform:* Alluvial fans
- *Parent material:* Alluvium derived from sandstone and shale

Typical profile

- *H1 - 0 to 14 inches:* silt loam
- *H2 - 14 to 41 inches:* silty clay loam
- *H3 - 41 to 60 inches:* silty clay

This corresponds in part, but same sandy material was seen. The description is generic, so the clay at the parcel is likely elastic silt. As there is fill on site, coarser sediments as well as concrete rubble and other fill materials are to be expected in the northern part of the parcel.

ALL AMERICAN GEOTECHNICAL, INC.

SITE VEGETATION

The site of the proposed development has been cleared to grass and scrub with the exception of isolated trees scattered on-site with some fringing trees and shrubs. The upper part has been mostly cleared as noted above. Fringing vegetation and growth along the property line to the southeast was mostly intact. The upper part of the lot was already cleared of most of the vegetation at the time of the pitting program. Areas in the mapped wetlands and fringing areas to the south of the proposed development are still vegetated but there is no evidence of landslides in these areas based on traverses.

PITTING

A total of six pits were dug and are described below. Please see site map after the text.

Pit 1

0-12" Brown sand. At 12" some concretion clots seen

12" – 6' Possibly ML as grain size is very fine. Grey layers are present and concretions with hematite mottling are present. Sample #1. The test results from MTC Labs indicates this is a sandy silt, with silt/clay (-200 sieve) fraction at 61.5% passing. Field tests indicate this is dominantly silt.

6' – 8' Picking up clay in grey material. There is silt/clay deposition to 8' T.D. Sample #2 is from this interval. This was classified as **MH** – *Elastic silt with sand*. While silt and sand dominate, there is a potential that there is a clay fraction of 38.8%. Plasticity index was 23.2%. Liquid limit was 55.8%. This sample has likely a large fraction of clay.

Pit 2

0 – 18" Dry dusty grey silty sand/sandy silt. First mottling seen at 18".

2' Material is clumping and excavating out in "plates." Composition appears silt-dominated.

2 ½' More mottling in greyer material – silt but minor clay present.

6' Heavily mottled – into richer clay layer w/manganese staining.

8' T.D. in material similar to same depth in Pit 1

Pit 3

0 – 5' Dry sandy silt

5' Takes on a clayey aspect as part of grey material with mottling

7' T.D. "Plates" of clay/mottled material sheen of water on surface of "plate."

ALL AMERICAN GEOTECHNICAL, INC.

Pit 4

0 to 3' or 4' Silty sand with gravel. Dark brown. Likely fill.

5' Still the same but with small concretions. Looks like the native as seen in the top of Pits 1 to 3.

6' – 7' Manganese in deposits. No clay yet except in minor “blobs.”

T.D. 8' Native silt/sand with clay. Abundant manganese stain.

Pit 5

Soil is mixed with concrete and brick

T.D. 2 ½' Heavy concrete chunks in soil. No further progress.

Pit 6

0 – 4' Apparent sand/silt dominant fill.

4' Brown fine-grained native material

6' – 8' Sample #3. (Misabeled Pit 2 by MTC). This sample is again a MH – *Sandy elastic silt*. The silt/clay fraction was -67.7%. Clays were only found to be 9.7% with the Plastic Index of 12%. The liquid limit was. 34.9%. This is a silt.

Note that buried turf was found at 5' or 6'. Appears surface was pushed over and buried under a layer of import fill. (?)

The results of the tests of sample #1, #2, and #3 indicate this site is typical of the Logan Hill weathered “rind” and landslides derived from this material. It is a silt/clay mix with sand present all, in varying proportions. From the field work and lab analyses it is evident that the material sampled and described as “clay” in the notes is dominantly elastic silt.

The presence of fill in Pits 5 and 6 indicates that the fill that anecdotally was shoved into place from Hosanna Lane south is indeed prevalent in the development area of the parcel. At least 3 to 4 feet of fill was also found in pit 4. As the composition and compaction of this fill is unknown for the entire site, it is the task of the builders to insure that the footings they place are on competent and unyielding soil or structural fill at the individual building sites.

SITE WORK

Any material that is clearly fill may be built on if it is removed to a solid base and developed with structural fill. The removed existing fill must be disposed of in a manner in accord with local regulations. The native

ALL AMERICAN GEOTECHNICAL, INC.

material is too fine-grained to be used as structural fill for buildings, but it is suitable for landscaping and non-structural backfill.

Although the material is predominantly silt, the classification considers it elastic silt and there is the possibility of some clay present. Firm silts and stiff clays can easily be developed at 1500 psf or greater (See "Conclusions, below), but wetting conditions can be critical in this case. The slope of the parcel, while not considered liable to deep-seated failure, is subject to creep and possible low-angle failure especially with applied loads. On the multiplex unit, keying of load-bearing slabs is recommended, and the spread footings should be designed to insure movement is resisted on the downslope side.

In these fine grained-materials, fabric would be advised for placement between the road subgrade and the engineered surface. There is no guarantee that if the road is to be paved that there shall be no infiltration into that area. If the design appears that water may enter and flow downslope, saturating the subgrade, then fabric is recommended to prevent the removal of fines and the subsequent settlement of the road.

Fabric is not considered necessary "beneath buildings." Adequate drainage and sufficiently designed footings in the fine-grained material are sufficient to prevent water infiltration and possible settlement. The concern is not so much swelling in clays, but simple washing out of fine-grained sediments which are nearly everything found on site where there isn't concrete rubble and other external fill. The Engineer of Record is assumed to be competent enough to keep the sub-grade and footings dry. It is on the EoR to determine the site-specific work needed to develop the parcel.

A vapor barrier is recommended beneath all slabs. This should be upon a gravel pad or as determined by the EoR.

CONCLUSIONS

The area is on landslide deposits which includes elastic silt and copious subsequent fill locally. The slope is low-angle, so all care needs to be done to ensure each building site is on competent deposits or structural fill.

In the case of the multiplex, it is recommended that design elements in the footing ensure the structure does not move en bloc downslope, although this is unlikely.

The material, as tested, would allow a bearing strength of 2200 lbs/ft². This is derived as the lower end of all three formulae presented on page 21 in the appendix: Terzaghi, Meyerhof, and Hansen.

Lateral pressures are:

Phi angle	25
ko	0.577
ka	0.406
kp	2.46

Based on the results of the site visits, pitting, and an extensive literature search, the parcel does not appear to pose a deep-seated landslide hazard. This determination is subject to change if, in construction, a glide

ALL AMERICAN GEOTECHNICAL, INC.

plane develops or there is mass wasting. Such an eventuality is not considered likely. Shallow creep is, however, possible and, due to the nature of the soils, moisture control shall be very important.

REPORT LIMITATIONS AND GUIDELINES FOR USE

We have prepared this report for the exclusive use of Fuller Designs and their authorized agents for the proposed building location in Lewis County, Washington. Within the limitations of scope, schedule and budget, our services have been executed in accordance with generally accepted practices in the field of geotechnical engineering in this area at the time this report was prepared. No warranty or other conditions, expressed or implied, should be understood.

READ THESE PROVISIONS CLOSELY

Some clients, design professionals, and contractors may not recognize that the geoscience practices (geotechnical engineering or geology) are far less exact than other engineering and natural science disciplines. This lack of understanding can create unrealistic expectations that could lead to disappointments, claims and disputes. All American Geotechnical includes these explanatory “limitations” provisions in our reports to help reduce such risks.

The equipment, techniques and personnel used to perform an environmental study differ significantly from those used to perform a geotechnical or geologic study and vice versa. For that reason, geotechnical engineering or geologic reporting does not usually relate any environmental findings, conclusions or recommendations; e.g., about the likelihood of encountering underground storage tanks or regulated contaminants. Similarly, environmental reports are not used to address geotechnical or geologic concerns regarding a specific project.

REPORT LIMITATIONS AND GUIDELINES FOR USE

We have prepared this report for the exclusive use of Aaron Fuller and his authorized agents for the proposed building location in Lewis County, Washington. Within the limitations of scope, schedule and budget, our services have been executed in accordance with generally accepted practices in the field of geotechnical engineering in this area at the time this report was prepared. No warranty or other conditions, expressed or implied, should be understood.


READ THESE PROVISIONS CLOSELY

Some clients, design professionals, and contractors may not recognize that the geoscience practices (geotechnical engineering or geology) are far less exact than other engineering and natural science disciplines. This lack of understanding can create unrealistic expectations that could lead to disappointments, claims and disputes. All American Geotechnical includes these explanatory “limitations” provisions in our reports to help reduce such risks.

ALL AMERICAN GEOTECHNICAL, INC.

The equipment, techniques and personnel used to perform an environmental study differ significantly from those used to perform a geotechnical or geologic study and vice versa. For that reason, geotechnical engineering or geologic reporting does not usually relate any environmental findings, conclusions or recommendations; e.g., about the likelihood of encountering underground storage tanks or regulated contaminants. Similarly, environmental reports are not used to address geotechnical or geologic concerns regarding a specific project.

Respectfully Submitted,
GEOTECHNICAL TESTING LABORATORY



Curtis D. Cushman, L.G., L.E.G.
Senior Engineering Geologist

Curtis Dean Cushman

ALL AMERICAN GEOTECHNICAL, INC.

REFERENCES

MAPS

DeLorme 3-D TopoQuads (2002), Source Data USGS, Yarmouth, Maine.

Palmer, Magsino, Poelstra, Bilderback, Folger, and Niggemann (September 2004), *The Liquefaction Susceptibility Map of Lewis County, Washington*, published by Washington State Department of Natural Resources.

Palmer, Magsino, Bilderback, Poelstra, Folger, and Niggemann (September 2004), *The Site Class Map of Lewis County, Washington*, published by Washington State Department of Natural Resources.

Rogers, A. M., Walsh, T. J., Kockelman, W. J., and Priest, G. R. (1996), *Map showing known or suspected faults with quaternary displacement in the Pacific Northwest*, published by U.S. Geological Survey OFR 91-441-O, Plate 1, scale 1:2,000,000.

Schasse, Henry (1987), *Geologic Map of the Centralia Quadrangle, Washington* published by the Washington State Department of Natural Resources OF 87-11

Walsh, Korosec, Phillips, Logan, and Schasse (1987), *Geological Map of Washington – Southwest Quadrant* (Geological Map GM-34), published by Washington State Department of Natural Resources.

PUBLICATIONS

ASTM International (2005), *Annual Book of Standards 2005, Section 4, Volume 4.08*, published by ASTM International, West Conshohocken, Pennsylvania.

Bloom (1991), *Geomorphology*, published by Prentice-Hall, Inc., Upper Saddle River, New Jersey.

International Code Council, Inc. (2006), *2006 International Building Code*, published by International Code Council, Inc.

Ness, Fowler, Parvin (1987), *The Soil Survey of Lewis County, Washington, USDA Soil Conservation Service*, in cooperation with the United States Department of Agriculture, and Washington Agricultural Experimental Station, and the Soils Conservation Service.

Parks, Neal, Koloski, Laprade, Molinari, Butler, and Lorentson (November 2006), *Guidelines for Preparing Engineering Geology Reports in Washington*, published by Washington State Geologist Licensing Board, Olympia, Washington.

Sowers (1979), *Introductory Soil Mechanics and Foundations: Geotechnical Engineering*, Macmillan Publishing Co., Inc.

WEBSITES (FOUND COMMONLY ON GIS, WA GEO PORTAL, USDA WSS, AND OTHERS)

Lewis County Government Information Services
(<http://www.co.lewis.wa.us>)

Puget Sound Lidar Consortium (Through the Washington Geologic Portal)
(<http://pugetsoundlidar.ess.washington.edu/lidardata/index.html>)

Slope Stabilization Erosion Control Using Vegetation A Manual of Practice for Coastal Bluff
(<http://www.ecy.wa.gov/biblio/9330.html>)

United States Department of Agriculture Natural Resource Conservation Service
(<http://soildatamart.nrcs.usda.gov>)

Washington Administrative Code

ALL AMERICAN GEOTECHNICAL, INC.

(<http://apps.leg.wa.gov/wac/>)

Washington Department of Ecology


(<http://apps.ecy.wa.gov/welllog>)

(<https://fortress.wa.gov/ecy/coastalatlascviewer.htm>)

ALL AMERICAN GEOTECHNICAL, INC.


SAMPLING LOCATIONS

7-13-2021 program pit locations



7/15/2021, 8:44:05 PM

1:1,128

 Parcels

0 50 100 200 ft
NAD 1983 StatePlane Washington South FIPS 4602 Feet




Lewis County does not guarantee the accuracy of the information shown on this map and is not responsible for any use or misuse by others regarding this material. It is provided for general informational purposes only. This map does not meet legal, engineering, or survey standards. Please practice due diligence and consult with licensed experts before making decisions.


© Lewis County GIS | 2019 Imagery © Pictometry & Lewis County

ALL AMERICAN GEOTECHNICAL, INC.

LABORATORY RESULTS

SIEVE REPORT -- PIT 1 @ 6-FT BGS

Project: Q.C. All American Geotechnical - 2021 Project #: 21S031 Client: All American Geotechnical, Inc. Source: Jackson Pit-1 @ 6 ft, sample #1 Sample#: B21-1067		Date Received: 13-Jul-21 Sampled By: Client Date Tested: 16-Jul-21 Tested By: C. Kriss		Visual Soils Classification Silt with Sand Sample Color: brown		 ACCREDITED Certificate #: 1366.01	
ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281							
Specifications No Specs Sample Meets Specs ? N/A		D ₍₅₎ = 0.006 mm D ₍₁₀₎ = 0.012 mm D ₍₁₅₎ = 0.018 mm D ₍₃₀₎ = 0.037 mm D ₍₅₀₎ = 0.061 mm D ₍₆₀₎ = 0.073 mm D ₍₉₀₎ = 1.343 mm Dust Ratio = 66/91		% Gravel = 1.7% % Sand = 36.8% % Silt & Clay = 61.5% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture % , 1 Face = n/a Fracture % , 2+ Faces = n/a		Coeff. of Curvature, C _c = 1.50 Coeff. of Uniformity, C _u = 6.00 Fineness Modulus = 0.82 Plastic Limit = n/a Moisture %, as sampled = n/a Req'd Sand Equivalent = Req'd Fracture % , 1 Face = Req'd Fracture % , 2+ Faces =	
ASTM C136, ASTM D6913, ASTM C117							
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min		
US	Metric						
12.00"	300.00	100%	100%	100.0%	0.0%		
10.00"	250.00	100%	100%	100.0%	0.0%		
8.00"	200.00	100%	100%	100.0%	0.0%		
6.00"	150.00	100%	100%	100.0%	0.0%		
4.00"	100.00	100%	100%	100.0%	0.0%		
3.00"	75.00	100%	100%	100.0%	0.0%		
2.50"	63.00	100%	100%	100.0%	0.0%		
2.00"	50.00	100%	100%	100.0%	0.0%		
1.75"	45.00	100%	100%	100.0%	0.0%		
1.50"	37.50	100%	100%	100.0%	0.0%		
1.25"	31.50	100%	100%	100.0%	0.0%		
1.00"	25.00	100%	100%	100.0%	0.0%		
3/4"	19.00	100%	100%	100.0%	0.0%		
5/8"	16.00	100%	100%	100.0%	0.0%		
1/2"	12.50	100%	100%	100.0%	0.0%		
3/8"	9.50	100%	100%	100.0%	0.0%		
1/4"	6.30	100%	99%	100.0%	0.0%		
#4	4.75	98%	98%	100.0%	0.0%		
#8	2.36	94%	94%	100.0%	0.0%		
#10	2.00	94%	94%	100.0%	0.0%		
#16	1.18	89%	89%	100.0%	0.0%		
#20	0.850	87%	87%	100.0%	0.0%		
#30	0.600	86%	86%	100.0%	0.0%		
#40	0.425	85%	85%	100.0%	0.0%		
#50	0.300	79%	79%	100.0%	0.0%		
#60	0.250	77%	77%	100.0%	0.0%		
#80	0.180	74%	74%	100.0%	0.0%		
#100	0.150	72%	72%	100.0%	0.0%		
#140	0.106	66%	66%	100.0%	0.0%		
#170	0.090	64%	64%	100.0%	0.0%		
#200	0.075	61.5%	61.5%	100.0%	0.0%		



Copyright Spens Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.


Comments: _____

Reviewed by: Meghan Blodgett-Carrillo



ALL AMERICAN GEOTECHNICAL, INC.

HYDROMETER REPORT -- PIT 1 @ 8-FT BGS

Project: Q.C. All American Geotechnical - 2021 Project #: 21S031 Client : All American Geotechnical, Inc. Source: Jackson Pit-1 @ 8 ft, sample #2 Sample#: B21-1068	Date Received: 13-Jul-21 Sampled By: Client Date Tested: 16-Jul-21 Tested By: C. Kriss	Unified Soils Classification System MH, Elastic Silt with Sand Sample Color brown																																																																											
ASTM D422, HYDROMETER ANALYSIS		ASTM C136																																																																											
Assumed Sp Gr : 2.70 Sample Weight: 50.10 grams Hydrosopic Moist.: 7.75% Adj. Sample Wgt : 46.50 grams		Sieve Analysis Grain Size Distribution																																																																											
 ACCREDITED Certificate #: 1366.01		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>98%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>89%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>80.6%</td><td>0.075 mm</td></tr> <tr><td colspan="2">Silts</td><td>79.8%</td><td>0.074 mm</td></tr> <tr><td colspan="2"></td><td>61.4%</td><td>0.050 mm</td></tr> <tr><td colspan="2"></td><td>48.6%</td><td>0.020 mm</td></tr> <tr><td colspan="2">Clays</td><td>38.8%</td><td>0.005 mm</td></tr> <tr><td colspan="2"></td><td>33.8%</td><td>0.002 mm</td></tr> <tr><td colspan="2">Colloids</td><td>25.1%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	99%	0.850 mm	#40	98%	0.425 mm	#100	89%	0.150 mm	#200	80.6%	0.075 mm	Silts		79.8%	0.074 mm			61.4%	0.050 mm			48.6%	0.020 mm	Clays		38.8%	0.005 mm			33.8%	0.002 mm	Colloids		25.1%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																											
3.0"	100%	75.000 mm																																																																											
2.0"	100%	50.000 mm																																																																											
1.5"	100%	37.500 mm																																																																											
1.25"	100%	31.500 mm																																																																											
1.0"	100%	25.000 mm																																																																											
3/4"	100%	19.000 mm																																																																											
5/8"	100%	16.000 mm																																																																											
1/2"	100%	12.500 mm																																																																											
3/8"	100%	9.500 mm																																																																											
1/4"	100%	6.300 mm																																																																											
#4	100%	4.750 mm																																																																											
#10	100%	2.000 mm																																																																											
#20	99%	0.850 mm																																																																											
#40	98%	0.425 mm																																																																											
#100	89%	0.150 mm																																																																											
#200	80.6%	0.075 mm																																																																											
Silts		79.8%	0.074 mm																																																																										
		61.4%	0.050 mm																																																																										
		48.6%	0.020 mm																																																																										
Clays		38.8%	0.005 mm																																																																										
		33.8%	0.002 mm																																																																										
Colloids		25.1%	0.001 mm																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading Minutes</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>2</td><td>23</td><td>48.9%</td><td>0.0336 mm</td></tr> <tr><td>5</td><td>23</td><td>48.9%</td><td>0.0213 mm</td></tr> <tr><td>15</td><td>22</td><td>46.8%</td><td>0.0124 mm</td></tr> <tr><td>30</td><td>20</td><td>42.5%</td><td>0.0088 mm</td></tr> <tr><td>60</td><td>19.5</td><td>41.5%</td><td>0.0063 mm</td></tr> <tr><td>250</td><td>16.5</td><td>35.1%</td><td>0.0031 mm</td></tr> <tr><td>1440</td><td>15.5</td><td>33.0%</td><td>0.0013 mm</td></tr> </tbody> </table>		Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter	2	23	48.9%	0.0336 mm	5	23	48.9%	0.0213 mm	15	22	46.8%	0.0124 mm	30	20	42.5%	0.0088 mm	60	19.5	41.5%	0.0063 mm	250	16.5	35.1%	0.0031 mm	1440	15.5	33.0%	0.0013 mm																																												
Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																										
2	23	48.9%	0.0336 mm																																																																										
5	23	48.9%	0.0213 mm																																																																										
15	22	46.8%	0.0124 mm																																																																										
30	20	42.5%	0.0088 mm																																																																										
60	19.5	41.5%	0.0063 mm																																																																										
250	16.5	35.1%	0.0031 mm																																																																										
1440	15.5	33.0%	0.0013 mm																																																																										
% Gravel: 0.0% Liquid Limit: 55.8 % % Sand: 19.4% Plastic Limit: 32.6 % % Silt: 41.7% Plasticity Index: 23.2 % % Clay: 38.8%																																																																													
USDA Soil Textural Classification																																																																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>% Sand:</td> <td>Particle Size 2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </tbody> </table>		% Sand:	Particle Size 2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																						
% Sand:	Particle Size 2.0 - 0.05 mm																																																																												
% Silt:	0.05 - 0.002 mm																																																																												
% Clay:	< 0.002 mm																																																																												
USDA Soil Textural Classification																																																																													
Clay Loam																																																																													

All results apply only to actual locations and materials tested. As a minimal protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____

Meghan Blodgett-Carrillo




ALL AMERICAN GEOTECHNICAL, INC.

ASTM D4318- LIQUID LIMIT, PLASTIC LIMIT, & PLASTICITY INDEX OF SOILS -- PIT 1 @ 8-FT BGS

Project: Q.C. All American Geotechnical - 2021 Project #: 21S031 Client: All American Geotechnical, Inc. Source: Jackson Pit-1 @ 8 ft, sample #2 Sample #: B21-1068	Date Received: 13-Jul-21 Sampled By: Client Date Tested: 16-Jul-21 Tested By: C. Kriss	Unified Soils Classification System MH, Elastic Silt with Sand Sample Color brown
---	---	--

Liquid Limit Determination

	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	44.61					
Weight of Dry Soils + Pan:	38.89					
Weight of Pan:	28.63					
Weight of Dry Soils:	10.26					
Weight of Moisture:	5.72					
% Moisture:	55.8 %					
Number of Blows:	30					




Liquid Limit @ 25 Blows: 56 %
 Plastic Limit: 33 %
 Plasticity Index, I_p: 23 %


Plastic Limit Determination

	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	37.72	37.19				
Weight of Dry Soils + Pan:	35.86	35.42				
Weight of Pan:	30.12	30.02				
Weight of Dry Soils:	5.74	5.40				
Weight of Moisture:	1.86	1.77				
% Moisture:	32.4 %	32.8 %				

Plasticity Chart



Liquid Limit



Copyright Speers Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____


Reviewed by: _____


Meghan Blodgett-Carrillo



ALL AMERICAN GEOTECHNICAL, INC.

SIEVE REPORT -- PIT 2 @ 6-FT BGS

Project: Q.C. All American Geotechnical - 2021 Project #: 21S031 Client: All American Geotechnical, Inc. Source: Jackson Pit-2 @ 6 ft, sample #3 Sample#: B21-1069		Date Received: 13-Jul-21 Sampled By: Client Date Tested: 16-Jul-21 Tested By: C. Kriss		Unified Soils Classification System MH, Sandy Elastic Silt Sample Color: gray-brown		 ACCREDITED Certificate #: 1366.01	
ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281							
Specifications No Specs Sample Meets Specs ? N/A		D ₍₅₎ = 0.002 mm D ₍₁₀₎ = 0.005 mm D ₍₁₅₎ = 0.010 mm D ₍₃₀₎ = 0.043 mm D ₍₅₀₎ = 0.060 mm D ₍₆₀₎ = 0.068 mm D ₍₈₀₎ = 1.677 mm Dust Ratio = 11/14		% Gravel = 4.4% % Sand = 27.9% % Silt & Clay = 67.7% Liquid Limit = 34.9% Plasticity Index = 11.7% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a		Coeff. of Curvature, C _c = 5.05 Coeff. of Uniformity, C _u = 13.06 Fineness Modulus = 0.83 Plastic Limit = 23.2% Moisture %, as sampled = n/a Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =	
ASTM C136, ASTM D6913, ASTM C117							
		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min		
Sieve Size	US	Metric					
12.00"		300.00			100.0%	100.0%	0.0%
10.00"		250.00			100.0%	100.0%	0.0%
8.00"		200.00			100.0%	100.0%	0.0%
6.00"		150.00			100.0%	100.0%	0.0%
4.00"		100.00			100.0%	100.0%	0.0%
3.00"		75.00			100.0%	100.0%	0.0%
2.50"		63.00			100.0%	100.0%	0.0%
2.00"		50.00	100%		100.0%	100.0%	0.0%
1.75"		45.00			100.0%	100.0%	0.0%
1.50"		37.50			100.0%	100.0%	0.0%
1.25"		31.50			100.0%	100.0%	0.0%
1.00"		25.00	100%		100.0%	100.0%	0.0%
3/4"		19.00	100%		100.0%	100.0%	0.0%
5/8"		16.00			100.0%	100.0%	0.0%
1/2"		12.50	100%		100.0%	100.0%	0.0%
3/8"		9.50	99%		100.0%	100.0%	0.0%
1/4"		6.30	96%		100.0%	100.0%	0.0%
#4		4.75	96%		100.0%	100.0%	0.0%
#8		2.36	92%		100.0%	100.0%	0.0%
#10		2.00	91%		100.0%	100.0%	0.0%
#16		1.18	89%		100.0%	100.0%	0.0%
#20		0.850	88%		100.0%	100.0%	0.0%
#30		0.600	87%		100.0%	100.0%	0.0%
#40		0.425	86%		100.0%	100.0%	0.0%
#50		0.300	81%		100.0%	100.0%	0.0%
#60		0.250	79%		100.0%	100.0%	0.0%
#80		0.180	76%		100.0%	100.0%	0.0%
#100		0.150	75%		100.0%	100.0%	0.0%
#140		0.106	71%		100.0%	100.0%	0.0%
#170		0.090	69%		100.0%	100.0%	0.0%
#200		0.075	67.7%		100.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____


Reviewed by: *Meghan Blodgett-Carrillo*

 Meghan Blodgett-Carrillo



ALL AMERICAN GEOTECHNICAL, INC.

HYDROMETER REPORT -- PIT 2 @ 6-FT BGS

Project: Q.C. All American Geotechnical - 2021 Project #: 21S031 Client : All American Geotechnical, Inc. Source: Jackson Pit-2 @ 6 ft, sample #3 Sample#: B21-1069	Date Received: 13-Jul-21 Sampled By: Client Date Tested: 16-Jul-21 Tested By: C. Kriss	Unified Soils Classification System MH, Sandy Elastic Silt Sample Color gray-brown																																																																																																											
ASTM D422, HYDROMETER ANALYSIS		ASTM C136																																																																																																											
Assumed Sp Gr : 2.70 Sample Weight: 50.09 grams Hydroscopic Moist.: 3.60% Adj. Sample Wgt : 48.35 grams		Sieve Analysis Grain Size Distribution																																																																																																											
 ACCREDITED Certificate #: 1366.01																																																																																																													
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>2</td><td>12</td><td>22.4%</td><td>0.0359 mm</td></tr> <tr><td>5</td><td>11.5</td><td>21.4%</td><td>0.0229 mm</td></tr> <tr><td>15</td><td>9</td><td>16.8%</td><td>0.0134 mm</td></tr> <tr><td>30</td><td>8</td><td>14.9%</td><td>0.0095 mm</td></tr> <tr><td>60</td><td>6.5</td><td>12.1%</td><td>0.0068 mm</td></tr> <tr><td>250</td><td>4</td><td>7.5%</td><td>0.0034 mm</td></tr> <tr><td>1440</td><td>2</td><td>3.7%</td><td>0.0014 mm</td></tr> </tbody> </table>	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	2	12	22.4%	0.0359 mm	5	11.5	21.4%	0.0229 mm	15	9	16.8%	0.0134 mm	30	8	14.9%	0.0095 mm	60	6.5	12.1%	0.0068 mm	250	4	7.5%	0.0034 mm	1440	2	3.7%	0.0014 mm	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>99%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>97%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>96%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>91%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>88%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>86%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>75%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>67.7%</td><td>0.075 mm</td></tr> <tr><td colspan="2">Silts</td><td></td></tr> <tr><td></td><td>66.6%</td><td>0.074 mm</td></tr> <tr><td></td><td>38.7%</td><td>0.050 mm</td></tr> <tr><td></td><td>20.0%</td><td>0.020 mm</td></tr> <tr><td colspan="2">Clays</td><td></td></tr> <tr><td></td><td>9.7%</td><td>0.005 mm</td></tr> <tr><td></td><td>4.8%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>2.6%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	99%	9.500 mm	1/4"	97%	6.300 mm	#4	96%	4.750 mm	#10	91%	2.000 mm	#20	88%	0.850 mm	#40	86%	0.425 mm	#100	75%	0.150 mm	#200	67.7%	0.075 mm	Silts				66.6%	0.074 mm		38.7%	0.050 mm		20.0%	0.020 mm	Clays				9.7%	0.005 mm		4.8%	0.002 mm	Colloids	2.6%	0.001 mm
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																										
2	12	22.4%	0.0359 mm																																																																																																										
5	11.5	21.4%	0.0229 mm																																																																																																										
15	9	16.8%	0.0134 mm																																																																																																										
30	8	14.9%	0.0095 mm																																																																																																										
60	6.5	12.1%	0.0068 mm																																																																																																										
250	4	7.5%	0.0034 mm																																																																																																										
1440	2	3.7%	0.0014 mm																																																																																																										
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																											
3.0"	100%	75.000 mm																																																																																																											
2.0"	100%	50.000 mm																																																																																																											
1.5"	100%	37.500 mm																																																																																																											
1.25"	100%	31.500 mm																																																																																																											
1.0"	100%	25.000 mm																																																																																																											
3/4"	100%	19.000 mm																																																																																																											
5/8"	100%	16.000 mm																																																																																																											
1/2"	100%	12.500 mm																																																																																																											
3/8"	99%	9.500 mm																																																																																																											
1/4"	97%	6.300 mm																																																																																																											
#4	96%	4.750 mm																																																																																																											
#10	91%	2.000 mm																																																																																																											
#20	88%	0.850 mm																																																																																																											
#40	86%	0.425 mm																																																																																																											
#100	75%	0.150 mm																																																																																																											
#200	67.7%	0.075 mm																																																																																																											
Silts																																																																																																													
	66.6%	0.074 mm																																																																																																											
	38.7%	0.050 mm																																																																																																											
	20.0%	0.020 mm																																																																																																											
Clays																																																																																																													
	9.7%	0.005 mm																																																																																																											
	4.8%	0.002 mm																																																																																																											
Colloids	2.6%	0.001 mm																																																																																																											
USDA Soil Textural Classification																																																																																																													
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>% Sand:</th> <th>Particle Size</th> </tr> </thead> <tbody> <tr><td>27.9%</td><td>2.0 - 0.05 mm</td></tr> <tr><td>58.0%</td><td>0.05 - 0.002 mm</td></tr> <tr><td>9.7%</td><td>< 0.002 mm</td></tr> </tbody> </table>	% Sand:	Particle Size	27.9%	2.0 - 0.05 mm	58.0%	0.05 - 0.002 mm	9.7%	< 0.002 mm																																																																																																				
% Sand:	Particle Size																																																																																																												
27.9%	2.0 - 0.05 mm																																																																																																												
58.0%	0.05 - 0.002 mm																																																																																																												
9.7%	< 0.002 mm																																																																																																												
USDA Soil Textural Classification Sandy Loam																																																																																																													

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____



Meghan Blodgett-Carrillo

Meghan Blodgett-Carrillo



ALL AMERICAN GEOTECHNICAL, INC.

ASTM D4318- LIQUID LIMIT, PLASTIC LIMIT, & PLASTICITY INDEX OF SOILS -- PIT 2 @ 6-FT BGS


Project: Q.C. All American Geotechnical - 2021 Project #: 21S031 Client: All American Geotechnical, Inc. Source: Jackson Pit-2 @ 6 ft. sample #3 Sample #: B21-1069	Date Received: 13-Jul-21 Sampled By: Client Date Tested: 16-Jul-21 Tested By: C. Kriss	Unified Soils Classification System MH, Sandy Elastic Silt Sample Color gray-brown				
Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	30.11	31.15	38.23			
Weight of Dry Soils + Pan:	27.36	28.09	32.98			
Weight of Pan:	19.47	19.94	19.47			
Weight of Dry Soils:	7.89	8.15	13.51			
Weight of Moisture:	2.75	3.06	5.25			
% Moisture:	34.9 %	37.6 %	38.9 %			
Number of Blows:	25	15	10			
Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	34.76	36.94				
Weight of Dry Soils + Pan:	33.64	35.62				
Weight of Pan:	28.33	30.40				
Weight of Dry Soils:	5.31	5.22				
Weight of Moisture:	1.12	1.32				
% Moisture:	21.1 %	25.3 %				
Plasticity Chart		Liquid Limit				
						
<small>Copyright Spears Engineering & Technical Services PS, 1996-98</small>						



Liquid Limit @ 25 Blows: 35 %
Plastic Limit: 23 %
Plasticity Index, I_p: 12 %

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by: 
Meghan Blodgett-Carrillo



ALL AMERICAN GEOTECHNICAL, INC.

BEARING ANALYSIS

UNIT WEIGHTS		lb	oz	decimal oz	7.125 lb/halfgal	14.25 lb/gallon	106.5974 lb/ft ³	Ny	Nc	Nq						
MH	clayey silts	7	2	0.125	7.125	14.25	106.5974	25°	10.12	25.13	12.72 Terzaghi					
MH	200 Cohesion	7	2	0.125	7.125	14.25	106.5974	25°	6.77	20.72	10.66 Meyerhof					
MH	200 Cohesion	7	2	0.125	7.125	14.25	106.5974	25°	6.76	20.72	10.66 Hansen					
BEARING		1/2' y *	B *	Ny	+ c *	Nc	25.13 +	+	(pq+ ignored)	y *	Df * Nq)	2	12.72	Bearing	F. O. S.	ULTIMATE BEARING
0.5	107	1	10.12	+	200	25.13	+	0	106.5974	2	12.72	8277.221	3	2759.074	Terzaghi	
0.5	107	1	6.77	+	200	20.72	+	0	106.5974	2	10.66	6777.489	3	2259.163	Meyerhof	
0.5	107	1	6.76	+	200	20.72	+	0	106.5974	2	10.66	6776.956	3	2258.985	Hansen	