

HYDROGEN FUELING FACILITY

1697 Bishop Road
Chehalis, WA 98532

PREPARED FOR

Twin Transit

PREPARED BY

JSA CIVIL

Engineering | Planning | Management

111 TUMWATER BLVD SE, SUITE C210

TUMWATER, WA 98501

CONTACT: BRANDON JOHNSON, PE

PHONE: 360.269.6346

Contents

SECTION 1: PROJECT OVERVIEW.....	3
SECTION 2: SITE CONDITIONS	5
SECTION 3: OFF-SITE ANALYSIS AND REPORT.....	5
SECTION 4: PERMANENT STORMWATER CONTROL PLAN.....	5
SECTION 5: PERMITS	7
SECTION 6: CONSTRUCTION STORMWATER POLLUTION PREVENTION PLAN	7

JSA CIVIL
Engineering | Planning | Management

PROJECT ENGINEER'S CERTIFICATION

The technical material and data contained in these documents were prepared under the supervision and direction of the undersigned, whose seal, as a professional engineer to practice as such, is affixed below.



Brandon Johnson, PE
Principal

Date

SECTION 1: PROJECT OVERVIEW

This Stormwater Site Plan was prepared for the proposed Hydrogen Fueling Facility located at 1697 Bishop Road, Chehalis, WA 98532. This report was prepared to comply with the minimum technical standards and requirements that are set forth in the 2019 Department of Ecology Stormwater Management Manual for Western Washington (SWMMWW).

The proposed commercial development will be constructed on a portion of Lewis County Tax Parcel No. 017758002000. Specifically, the proposed site improvements include the following:

- Site preparation, grading, and erosion control activities
- Construction of hydrogen fueling facilities
- Construction of an impervious surface parking lot & access roadways
- Construction of on-site stormwater facilities
- Extension of utilities (sewer, water, power, cable, etc.)

The proposed project improvements will result in more than 5,000 ft² of new impervious surface area. According to the SWMMWW, Minimum Requirements 1-9 need to be addressed. The following table summarizes how each requirement will be met.

MINIMUM REQUIREMENT	COMPLIANCE WITH MINIMUM REQUIREMENT
#1 - Stormwater Site Plan	The contents of this report and the enclosed plans are intended to satisfy this requirement.
#2 - Construction SWPPP	A Construction SWPPP will be prepared at the time of final permitting.
#3 - Source Control of Pollution	If required, a Source Control Pollution Prevention Plan will be recorded against the property prior to certificate of occupancy.
#4 - Drainage Path Preservation	Preservation of the site's previously established natural drainage paths will be maintained to the maximum extent practicable.
#5 - Stormwater Management	List 2 from the SWMMWW will be implemented to meet the project's Low Impact Development (LID) requirements.
#6 - Runoff Treatment	More than 5,000 ft ² of new/replaced impervious surface area is proposed. A downstream, an
#7 - Flow Control	More than 10,000 ft ² of new/replaced impervious surface is proposed. Stormwater will be released off-site at the predeveloped flow rates.
#8 - Wetlands Protection	The proposed project improvements will not disturb existing mapped wetlands.
#9 - Operation & Maintenance	An Agreement to Maintain Stormwater Facilities will be recorded against the property, if required.

Table 1: Compliance with Minimum Technical Requirements

SECTION 2: SITE CONDITIONS

Existing Site Conditions

The subject parcel is approximately 23.28 acres of undeveloped property. The proposed improvements associated with this application will be positioned on approximately 1.94 acres of the parent parcel in the southern corner of the site, adjacent to Bishop Road. The developed portion of the site, generally, slopes east to west towards Bishop Road. According to FEMA mapping, the site is positioned in Zone X, an area of minimal flooding.

Soils Information

A geotechnical report will be completed for the project prior to final construction. For preliminary design, the SCS Web Soil Survey shows the soils to be Scamman Silty Clay Loam, a type C/D with little infiltration capacity. A detention facility that releases stormwater off-site at the predeveloped flow rates is proposed in-lieu of an infiltration facility.

SECTION 3: OFF-SITE ANALYSIS AND REPORT

On-site generated stormwater runoff from the proposed commercial development will be routed to an on-site detention facility, which will be released off-site to the north at the predeveloped flow rates. Historic off-site drainage courses will not be altered. Consequently, downstream impacts are not anticipated.

SECTION 4: PERMANENT STORMWATER CONTROL PLAN

Summary Section

The following tables identifies the different land-type designations and their respective areas for the on-site and off-site threshold discharge areas:

ON-SITE LAND TYPE DESIGNATIONS	AREA (ACRES)	% OF TOTAL AREA
Threshold Discharge Area	1.94	100.0%
Proposed Impervious Surface Area	1.27	65.5%
Proposed Landscaping & Storm Pond Area	0.67	34.5%

Low Impact Development Analysis

List #2 from *Table I-3.2* of the SWMMWW will be used for this project in lieu of meeting the LID Performance Standard.

JSACIVIL
Engineering | Planning | Management

SURFACE	BMP LID	FEASIBLE	INFEASIBILITY CRITERIA
Landscaped Areas	BMP T5.13	Yes	Post Construction Soil Quality & Depth - N/A

SURFACE	BMP LID	FEASIBLE	INFEASIBILITY CRITERIA
Roof Area	BMP T5.30	No	A minimum on-site forested or native vegetation flow path length of 100 feet cannot be achieved.
	BMP T5.10A	No	Per soils information, infiltration is infeasible.
	BMP T7.30	No	Per soils information, infiltration is infeasible.
	BMP 5.10B	No	A vegetated flowpath of at least 25 feet between dispersion BMP and property line is not feasible.
	BMP T5.10C	No	The connecting pipe discharged to a stormwater facility designed to meet Minimum Requirement 7.

SURFACE	BMP LID	FEASIBLE	INFEASIBILITY CRITERIA
Other Hardscapes	BMP T5.30	No	A minimum on-site forested or native vegetation flow path length of 100 feet cannot be achieved.
	BMP T5.15	No	New permeable pavement would be exposed to long-term excessive sediment deposition after construction.
	BMP T7.30	No	Per soils information, infiltration is infeasible.
	BMP T5.12	No	A vegetated flowpath of at least 25 feet between dispersion BMP and property line is not feasible.
	BMP T5.11	No	A vegetated flowpath of at least 25 feet between dispersion BMP and property line is not feasible.

Water Quality System

According to Volume I, Section 2.5.6, of the SWMMWW, Basic Treatment is required for the proposed project improvements. The project will utilize a treatment BMP downstream of the proposed detention facility. Clear Creek's 2021 Western Washington Hydrologic Modeling (WWHM) software was used to determine a 2yr flow rate of 0.0581 CFS (26.07 gpm). An MWS-Modular Wetland will be utilized to provide treatment per the WSDOE sizing requirements below:

- **Wetland Cell Surface Area:** WSDOE requires 1 SF of wetland cell surface area per gpm of treatment flow. The MWS-L-G-6.33-V contains 50sf of surface area, which is greater than the required 26 sf.
- **Pretreatment Filter:** WSDOE requires 2.1 gpm/sf of cartridge area. Each cartridge contains 25 SF of surface area, therefore 1 pretreatment cartridge is required.

Flow Control System

According to Volume I, Section 2.5.7, of the SWMMWW, stormwater discharges shall match developed discharge durations to predeveloped durations for the range of predeveloped discharge rates from 50% of the 2-year peak flow up to the full 50-year peak flow (i.e., the stream duration standard). WWHM was used to size the proposed detention facility. An infiltration rate was **not** applied for the design of the detention pond. The Detention WWHM report is enclosed as an appendix. Stormwater will be released off-site at the historic location. Refer to the civil engineering plans for additional design information.

SECTION 5: PERMITS

The following permits and approvals will need to be secured from Lewis County prior to beginning construction activities.

- State Environmental Policy Act (SEPA) Determination
- Site Plan Review
- Civil Construction Permit
- Building Permit
- WSDOE Notice of Intent

SECTION 6: CONSTRUCTION STORMWATER POLLUTION PREVENTION PLAN

A Construction Stormwater Pollution Prevention Plan will be prepared as part of the final construction documents.

APPENDIX 1

VICINITY MAP




JSACIVIL

Engineering | Planning | Management

111 Tumwater Blvd SE, Suite C210 | Tumwater, WA 98501

APPENDIX 2

FEMA MAP




JSACIVIL

Engineering | Planning | Management

111 Tumwater Blvd SE, Suite C210 | Tumwater, WA 98501

APPENDIX 3

SCS SOILS MAP



JSACIVIL

Engineering | Planning | Management

111 Tumwater Blvd SE, Suite C210 | Tumwater, WA 98501

APPENDIX 4

WWHM REPORT

JSACIVIL

Engineering | Planning | Management

111 Tumwater Blvd SE, Suite C210 | Tumwater, WA 98501

WWHM2012

PROJECT REPORT

General Model Information

Project Name: 114.004 Twin Transit

Site Name:

Site Address:

City:

Report Date: 9/29/2022

Gage: Olympia

Data Start: 1955/10/01

Data End: 2008/09/30

Timestep: 15 Minute

Precip Scale: 0.800

Version Date: 2019/09/13

Version: 4.2.17

POC Thresholds

Low Flow Threshold for POC1: 50 Percent of the 2 Year

High Flow Threshold for POC1: 50 Year

Landuse Basin Data

Predeveloped Land Use

Basin 1

Bypass: No

GroundWater: No

Pervious Land Use acre
C, Forest, Flat 1.94

Pervious Total 1.94

Impervious Land Use acre

Impervious Total 0

Basin Total 1.94

Element Flows To:

Surface Interflow Groundwater

Mitigated Land Use

Basin 1

Bypass:	No
GroundWater:	No
Pervious Land Use C, Lawn, Flat	acre 0.67
Pervious Total	0.67
Impervious Land Use PARKING FLAT	acre 1.27
Impervious Total	1.27
Basin Total	1.94

Element Flows To:

Surface Trapezoidal Pond 1	Interflow Trapezoidal Pond 1	Groundwater
-------------------------------	---------------------------------	-------------

Routing Elements

Predeveloped Routing

Mitigated Routing

Trapezoidal Pond 1

Bottom Length:	76.00 ft.
Bottom Width:	76.00 ft.
Depth:	5 ft.
Volume at riser head:	0.7283 acre-feet.
Side slope 1:	3 To 1
Side slope 2:	3 To 1
Side slope 3:	3 To 1
Side slope 4:	3 To 1
Discharge Structure	
Riser Height:	4 ft.
Riser Diameter:	18 in.
Notch Type:	Rectangular
Notch Width:	0.029 ft.
Notch Height:	1.225 ft.
Orifice 1 Diameter:	0.829 in. Elevation:0 ft.
Element Flows To:	
Outlet 1	Outlet 2

Pond Hydraulic Table


Stage(feet)	Area(ac.)	Volume(ac-ft.)	Discharge(cfs)	Infilt(cfs)
0.0000	0.132	0.000	0.000	0.000
0.0556	0.133	0.007	0.004	0.000
0.1111	0.134	0.014	0.006	0.000
0.1667	0.136	0.022	0.007	0.000
0.2222	0.137	0.030	0.008	0.000
0.2778	0.138	0.037	0.009	0.000
0.3333	0.139	0.045	0.010	0.000
0.3889	0.140	0.053	0.011	0.000
0.4444	0.142	0.061	0.012	0.000
0.5000	0.143	0.069	0.013	0.000
0.5556	0.144	0.076	0.013	0.000
0.6111	0.145	0.085	0.014	0.000
0.6667	0.146	0.093	0.015	0.000
0.7222	0.148	0.101	0.015	0.000
0.7778	0.149	0.109	0.016	0.000
0.8333	0.150	0.117	0.017	0.000
0.8889	0.151	0.126	0.017	0.000
0.9444	0.153	0.134	0.018	0.000
1.0000	0.154	0.143	0.018	0.000
1.0556	0.155	0.152	0.019	0.000
1.1111	0.156	0.160	0.019	0.000
1.1667	0.158	0.169	0.020	0.000
1.2222	0.159	0.178	0.020	0.000
1.2778	0.160	0.187	0.021	0.000
1.3333	0.162	0.196	0.021	0.000
1.3889	0.163	0.205	0.022	0.000
1.4444	0.164	0.214	0.022	0.000
1.5000	0.165	0.223	0.022	0.000
1.5556	0.167	0.232	0.023	0.000
1.6111	0.168	0.242	0.023	0.000
1.6667	0.169	0.251	0.024	0.000
1.7222	0.171	0.260	0.024	0.000

1.7778	0.172	0.270	0.024	0.000
1.8333	0.173	0.280	0.025	0.000
1.8889	0.175	0.289	0.025	0.000
1.9444	0.176	0.299	0.026	0.000
2.0000	0.177	0.309	0.026	0.000
2.0556	0.179	0.319	0.026	0.000
2.1111	0.180	0.329	0.027	0.000
2.1667	0.181	0.339	0.027	0.000
2.2222	0.183	0.349	0.027	0.000
2.2778	0.184	0.359	0.028	0.000
2.3333	0.186	0.369	0.028	0.000
2.3889	0.187	0.380	0.028	0.000
2.4444	0.188	0.390	0.029	0.000
2.5000	0.190	0.401	0.029	0.000
2.5556	0.191	0.411	0.029	0.000
2.6111	0.192	0.422	0.030	0.000
2.6667	0.194	0.433	0.030	0.000
2.7222	0.195	0.444	0.030	0.000
2.7778	0.197	0.455	0.031	0.000
2.8333	0.198	0.466	0.032	0.000
2.8889	0.200	0.477	0.035	0.000
2.9444	0.201	0.488	0.038	0.000
3.0000	0.202	0.499	0.042	0.000
3.0556	0.204	0.510	0.045	0.000
3.1111	0.205	0.522	0.050	0.000
3.1667	0.207	0.533	0.054	0.000
3.2222	0.208	0.545	0.059	0.000
3.2778	0.210	0.556	0.064	0.000
3.3333	0.211	0.568	0.069	0.000
3.3889	0.213	0.580	0.074	0.000
3.4444	0.214	0.592	0.079	0.000
3.5000	0.216	0.604	0.085	0.000
3.5556	0.217	0.616	0.090	0.000
3.6111	0.219	0.628	0.096	0.000
3.6667	0.220	0.640	0.101	0.000
3.7222	0.222	0.652	0.107	0.000
3.7778	0.223	0.665	0.112	0.000
3.8333	0.225	0.677	0.119	0.000
3.8889	0.226	0.690	0.126	0.000
3.9444	0.228	0.702	0.133	0.000
4.0000	0.229	0.715	0.140	0.000
4.0556	0.231	0.728	0.348	0.000
4.1111	0.232	0.741	0.728	0.000
4.1667	0.234	0.754	1.215	0.000
4.2222	0.235	0.767	1.778	0.000
4.2778	0.237	0.780	2.390	0.000
4.3333	0.238	0.793	3.024	0.000
4.3889	0.240	0.806	3.652	0.000
4.4444	0.242	0.820	4.246	0.000
4.5000	0.243	0.833	4.781	0.000
4.5556	0.245	0.847	5.240	0.000
4.6111	0.246	0.861	5.611	0.000
4.6667	0.248	0.874	5.897	0.000
4.7222	0.249	0.888	6.118	0.000
4.7778	0.251	0.902	6.393	0.000
4.8333	0.253	0.916	6.613	0.000
4.8889	0.254	0.930	6.825	0.000
4.9444	0.256	0.944	7.031	0.000

5.0000	0.257	0.959	7.231	0.000
5.0556	0.259	0.973	7.425	0.000

Analysis Results

POC 1



Predeveloped Landuse Totals for POC #1

Total Pervious Area: 1.94
Total Impervious Area: 0

Mitigated Landuse Totals for POC #1

Total Pervious Area: 0.67
Total Impervious Area: 1.27

Flow Frequency Method: Log Pearson Type III 17B

Flow Frequency Return Periods for Predeveloped. POC #1

Return Period	Flow(cfs)
2 year	0.060693
5 year	0.092837
10 year	0.112539
25 year	0.135272
50 year	0.150656
100 year	0.164799

Flow Frequency Return Periods for Mitigated. POC #1

Return Period	Flow(cfs)
2 year	0.036959
5 year	0.058137
10 year	0.075524
25 year	0.101784
50 year	0.12477
100 year	0.150958

Annual Peaks

Annual Peaks for Predeveloped and Mitigated. POC #1

Year	Predeveloped	Mitigated
1956	0.074	0.042
1957	0.102	0.031
1958	0.034	0.023
1959	0.044	0.030
1960	0.081	0.100
1961	0.061	0.039
1962	0.020	0.024
1963	0.086	0.069
1964	0.063	0.032
1965	0.052	0.028

1966	0.034	0.026
1967	0.068	0.031
1968	0.050	0.026
1969	0.026	0.025
1970	0.056	0.043
1971	0.071	0.047
1972	0.105	0.100
1973	0.057	0.065
1974	0.041	0.034
1975	0.096	0.025
1976	0.078	0.047
1977	0.014	0.019
1978	0.060	0.057
1979	0.078	0.024
1980	0.056	0.042
1981	0.080	0.032
1982	0.053	0.041
1983	0.085	0.029
1984	0.068	0.025
1985	0.023	0.025
1986	0.107	0.039
1987	0.120	0.076
1988	0.035	0.029
1989	0.044	0.023
1990	0.126	0.052
1991	0.158	0.107
1992	0.036	0.029
1993	0.025	0.022
1994	0.024	0.021
1995	0.069	0.031
1996	0.111	0.045
1997	0.063	0.062
1998	0.055	0.026
1999	0.077	0.075
2000	0.078	0.037
2001	0.012	0.019
2002	0.078	0.083
2003	0.033	0.025
2004	0.049	0.052
2005	0.057	0.025
2006	0.083	0.041
2007	0.067	0.119
2008	0.160	0.136

Ranked Annual Peaks

Ranked Annual Peaks for Predeveloped and Mitigated. POC #1

Rank	Predeveloped	Mitigated
1	0.1598	0.1356
2	0.1578	0.1186
3	0.1255	0.1067
4	0.1203	0.1000
5	0.1112	0.0998
6	0.1068	0.0825
7	0.1051	0.0760
8	0.1015	0.0750
9	0.0963	0.0694
10	0.0861	0.0655
11	0.0854	0.0616

12	0.0831	0.0571
13	0.0812	0.0522
14	0.0798	0.0520
15	0.0783	0.0475
16	0.0781	0.0466
17	0.0777	0.0445
18	0.0775	0.0432
19	0.0767	0.0424
20	0.0741	0.0423
21	0.0710	0.0414
22	0.0695	0.0406
23	0.0685	0.0391
24	0.0682	0.0391
25	0.0665	0.0372
26	0.0633	0.0339
27	0.0630	0.0320
28	0.0612	0.0317
29	0.0605	0.0310
30	0.0571	0.0309
31	0.0566	0.0308
32	0.0564	0.0303
33	0.0563	0.0295
34	0.0549	0.0292
35	0.0527	0.0291
36	0.0524	0.0280
37	0.0497	0.0262
38	0.0492	0.0259
39	0.0443	0.0256
40	0.0437	0.0255
41	0.0414	0.0253
42	0.0363	0.0252
43	0.0346	0.0251
44	0.0342	0.0247
45	0.0337	0.0246
46	0.0334	0.0241
47	0.0263	0.0240
48	0.0253	0.0231
49	0.0243	0.0226
50	0.0233	0.0216
51	0.0203	0.0206
52	0.0141	0.0193
53	0.0120	0.0189

Duration Flows

The Facility PASSED

Flow(cfs)	Predev	Mit	Percentage	Pass/Fail
0.0303	19217	16449	85	Pass
0.0316	17693	10768	60	Pass
0.0328	16174	9004	55	Pass
0.0340	14860	7951	53	Pass
0.0352	13639	7109	52	Pass
0.0364	12507	6466	51	Pass
0.0376	11467	5772	50	Pass
0.0389	10461	5133	49	Pass
0.0401	9593	4680	48	Pass
0.0413	8859	4256	48	Pass
0.0425	8168	3856	47	Pass
0.0437	7532	3537	46	Pass
0.0449	6941	3232	46	Pass
0.0461	6397	2974	46	Pass
0.0474	5910	2764	46	Pass
0.0486	5447	2607	47	Pass
0.0498	4999	2472	49	Pass
0.0510	4555	2314	50	Pass
0.0522	4193	2093	49	Pass
0.0534	3866	1968	50	Pass
0.0547	3570	1862	52	Pass
0.0559	3263	1712	52	Pass
0.0571	2972	1568	52	Pass
0.0583	2730	1464	53	Pass
0.0595	2505	1386	55	Pass
0.0607	2308	1311	56	Pass
0.0619	2117	1228	58	Pass
0.0632	1953	1148	58	Pass
0.0644	1801	1069	59	Pass
0.0656	1672	1000	59	Pass
0.0668	1558	937	60	Pass
0.0680	1449	883	60	Pass
0.0692	1345	842	62	Pass
0.0704	1258	805	63	Pass
0.0717	1169	775	66	Pass
0.0729	1096	738	67	Pass
0.0741	1012	701	69	Pass
0.0753	949	660	69	Pass
0.0765	886	633	71	Pass
0.0777	824	611	74	Pass
0.0790	785	593	75	Pass
0.0802	738	571	77	Pass
0.0814	695	549	78	Pass
0.0826	653	519	79	Pass
0.0838	610	495	81	Pass
0.0850	577	468	81	Pass
0.0862	544	445	81	Pass
0.0875	518	428	82	Pass
0.0887	491	411	83	Pass
0.0899	453	396	87	Pass
0.0911	422	378	89	Pass
0.0923	395	363	91	Pass
0.0935	367	346	94	Pass

0.0948	345	329	95	Pass
0.0960	324	312	96	Pass
0.0972	309	290	93	Pass
0.0984	289	269	93	Pass
0.0996	269	246	91	Pass
0.1008	252	227	90	Pass
0.1020	231	218	94	Pass
0.1033	216	207	95	Pass
0.1045	201	197	98	Pass
0.1057	180	177	98	Pass
0.1069	170	154	90	Pass
0.1081	160	143	89	Pass
0.1093	154	136	88	Pass
0.1106	142	130	91	Pass
0.1118	136	122	89	Pass
0.1130	132	117	88	Pass
0.1142	127	111	87	Pass
0.1154	122	105	86	Pass
0.1166	120	97	80	Pass
0.1178	116	70	60	Pass
0.1191	113	56	49	Pass
0.1203	110	54	49	Pass
0.1215	104	50	48	Pass
0.1227	100	48	48	Pass
0.1239	97	45	46	Pass
0.1251	93	41	44	Pass
0.1264	87	39	44	Pass
0.1276	84	35	41	Pass
0.1288	81	32	39	Pass
0.1300	77	25	32	Pass
0.1312	74	21	28	Pass
0.1324	69	18	26	Pass
0.1336	66	14	21	Pass
0.1349	62	7	11	Pass
0.1361	58	0	0	Pass
0.1373	53	0	0	Pass
0.1385	49	0	0	Pass
0.1397	42	0	0	Pass
0.1409	39	0	0	Pass
0.1421	36	0	0	Pass
0.1434	35	0	0	Pass
0.1446	33	0	0	Pass
0.1458	32	0	0	Pass
0.1470	27	0	0	Pass
0.1482	26	0	0	Pass
0.1494	23	0	0	Pass
0.1507	22	0	0	Pass

Water Quality

Water Quality BMP Flow and Volume for POC #1

On-line facility volume: 0 acre-feet

On-line facility target flow: 0 cfs.

Adjusted for 15 min: 0 cfs.

Off-line facility target flow: 0 cfs.

Adjusted for 15 min: 0 cfs.

LID Report

LID Technique	Used for Treatment ?	Total Volume Needs Treatment (ac-ft)	Volume Through Facility (ac-ft)	Infiltration Volume (ac-ft)	Cumulative Volume Infiltration Credit	Percent Volume Infiltrated	Water Quality	Percent Water Quality Treated	Comment
Trapezoidal Pond 1 POC	<input type="checkbox"/>	215.15			<input type="checkbox"/>	0.00			
Total Volume Infiltrated		215.15	0.00	0.00		0.00	0.00	0%	No Treat. Credit
Compliance with LID Standard 8% of 2-yr to 50% of 2-yr									Duration Analysis Result = Passed

Model Default Modifications

Total of 0 changes have been made.

PERLND Changes

No PERLND changes have been made.

IMPLND Changes


No IMPLND changes have been made.

Appendix

Predeveloped Schematic

		 Basin 1 1.94ac					

Mitigated Schematic



Predeveloped UCI File

```
RUN

GLOBAL
  WWHM4 model simulation
  START      1955 10 01          END      2008 09 30
  RUN INTERP OUTPUT LEVEL      3      0
  RESUME     0 RUN      1           UNIT SYSTEM      1
END GLOBAL

FILES
<File> <Un#> <-----File Name----->***  

<-ID->
WDM      26  114.004 Twin Transit.wdm
MESSU    25  Prel14.004 Twin Transit.MES
        27  Prel14.004 Twin Transit.L61
        28  Prel14.004 Twin Transit.L62
        30  POC114.004 Twin Transit1.dat
END FILES

OPN SEQUENCE
  INGRP          INDELT 00:15
    PERLND      10
    COPY        501
    DISPLAY     1
  END INGRP
END OPN SEQUENCE
DISPLAY
  DISPLAY-INFO1
    # - #-----Title----->***TRAN PIVL DIG1 FIL1 PYR DIG2 FIL2 YRND
    1             Basin 1           MAX           1   2   30   9
  END DISPLAY-INFO1
END DISPLAY
COPY
  TIMESERIES
    # - # NPT NMN ***
    1           1   1
  501         1   1
  END TIMESERIES
END COPY
GENER
  OPCODE
    # # OPCD ***
  END OPCODE
  PARM
    # # K ***
  END PARM
END GENER
PERLND
  GEN-INFO
    <PLS ><-----Name----->NBLKS  Unit-systems  Printer ***
    # - #
                  User t-series Engl Metr ***
                  in   out
    10  C, Forest, Flat       1   1   1   1   27   0
  END GEN-INFO
  *** Section PWATER***

ACTIVITY
  <PLS > ***** Active Sections *****
  # - # ATMP SNOW PWAT SED PST PWG PQAL MSTL PEST NITR PHOS TRAC ***
  10  0   0   1   0   0   0   0   0   0   0   0   0   0
END ACTIVITY

PRINT-INFO
  <PLS > ***** Print-flags *****
  # - # ATMP SNOW PWAT SED PST PWG PQAL MSTL PEST NITR PHOS TRAC *****
  10  0   0   4   0   0   0   0   0   0   0   0   0   1   9
END PRINT-INFO
```

```

PWAT-PARM1
<PLS > PWATER variable monthly parameter value flags ***
# - # CSNO RTOP UZFG VCS VUZ VNN VIFW VIRG VLE INFC HWT ***
10 0 0 0 0 0 0 0 0 0 0 0 0 0
END PWAT-PARM1

PWAT-PARM2
<PLS > PWATER input info: Part 2 ***
# - # ***FOREST LZSN INFILT LSUR SLSUR KVARY AGWRC
10 0 4.5 0.08 400 0.05 0.5 0.996
END PWAT-PARM2

PWAT-PARM3
<PLS > PWATER input info: Part 3 ***
# - # ***PETMAX PETMIN INFEXP INFILD DEEPFR BASETP AGWETP
10 0 0 2 2 0 0
END PWAT-PARM3

PWAT-PARM4
<PLS > PWATER input info: Part 4 ***
# - # CEPSC UZSN NSUR INTFW IRC LZETP ***
10 0.2 0.5 0.35 6 0.5 0.7
END PWAT-PARM4

PWAT-STATE1
<PLS > *** Initial conditions at start of simulation
           ran from 1990 to end of 1992 (pat 1-11-95) RUN 21 ***
# - # *** CEPS SURS UZS IFWS LZS AGWS GWVS
10 0 0 0 0 2.5 1 0
END PWAT-STATE1

END PERLND

IMPLND
GEN-INFO
<PLS ><-----Name-----> Unit-systems Printer ***
# - # User t-series Engl Metr ***
          in out ***
END GEN-INFO
*** Section IWATER***

ACTIVITY
<PLS > ***** Active Sections *****
# - # ATMP SNOW IWAT SLD IWG IQAL ***
END ACTIVITY

PRINT-INFO
<ILS > ***** Print-flags ***** PIVL PYR
# - # ATMP SNOW IWAT SLD IWG IQAL *****
END PRINT-INFO

IWAT-PARM1
<PLS > IWATER variable monthly parameter value flags ***
# - # CSNO RTOP VRS VNN RTLI ***
END IWAT-PARM1

IWAT-PARM2
<PLS > IWATER input info: Part 2 ***
# - # *** LSUR SLSUR NSUR RETSC
END IWAT-PARM2

IWAT-PARM3
<PLS > IWATER input info: Part 3 ***
# - # ***PETMAX PETMIN
END IWAT-PARM3

IWAT-STATE1
<PLS > *** Initial conditions at start of simulation
# - # *** RETS SURS
END IWAT-STATE1

```

```

END IMPLND

SCHEMATIC
<-Source->          <-Area-->      <-Target->    MBLK   ***
<Name> #             <-factor->      <Name> #     Tbl#   ***
Basin 1***           1.94        COPY    501     12
PERLND 10            1.94        COPY    501     13

*****Routing*****
END SCHEMATIC

NETWORK
<-Volume-> <-Grp> <-Member-><-Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> #           <Name> # #<-factor->strg <Name> # #     <Name> # #   ***
COPY    501 OUTPUT MEAN    1 1     48.4       DISPLAY 1      INPUT  TIMSER 1

<-Volume-> <-Grp> <-Member-><-Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> #           <Name> # #<-factor->strg <Name> # #     <Name> # #   ***
END NETWORK

RCHRES
GEN-INFO
  RCHRES      Name       Nexits   Unit Systems   Printer      ***
  # - #-----><---> User T-series Engl Metr LKFG
                           in   out                  ***

END GEN-INFO
*** Section RCHRES***

ACTIVITY
<PLS > ***** Active Sections *****
# - # HYFG ADFG CNFG HTFG SDFG GQFG OXFG NUFG PKFG PHFG ***
END ACTIVITY

PRINT-INFO
<PLS > ***** Print-flags *****
# - # HYDR ADCA CONS HEAT SED GQL OXRX NUTR PLNK PHCB PIVL PYR
END PRINT-INFO

HYDR-PARM1
  RCHRES Flags for each HYDR Section
  # - # VC A1 A2 A3 ODFVFG for each *** ODGTFG for each
    FG FG FG FG possible exit *** possible exit
    * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
  END HYDR-PARM1

HYDR-PARM2
  # - # FTABNO      LEN      DELTH      STCOR      KS      DB50      ***
  <----><----><----><----><----><----><----><---->
END HYDR-PARM2

HYDR-INIT
  RCHRES Initial conditions for each HYDR section
  # - # *** VOL      Initial value of COLIND      Initial value of OUTDGT
    *** ac-ft      for each possible exit      for each possible exit
  <----><----> <----><----><----><----> *** <----><----><----><---->
END HYDR-INIT
END RCHRES

SPEC-ACTIONS
END SPEC-ACTIONS
FTABLES
END FTABLES

EXT SOURCES
<-Volume-> <Member> SsysSgap<-Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> # <Name> # tem strg<-factor->strg <Name> # #     <Name> # #   ***
WDM      2 PREC      ENGL      0.8      PERLND  1 999 EXTNL  PREC
WDM      2 PREC      ENGL      0.8      IMPLND  1 999 EXTNL  PREC

```

```

WDM      1 EVAP      ENGL      0.76          PERLND     1 999 EXTNL    PETINP
WDM      1 EVAP      ENGL      0.76          IMPLND     1 999 EXTNL    PETINP

END EXT SOURCES

EXT TARGETS
<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Volume-> <Member> Tsys Tgap Amd ***
<Name> # <Name> # #<-factor->strg <Name> # <Name> tem strg strg***  

COPY 501 OUTPUT MEAN 1 1 48.4 WDM 501 FLOW ENGL REPL
END EXT TARGETS

MASS-LINK
<Volume> <-Grp> <-Member-><--Mult--> <Target> <-Grp> <-Member->***  

<Name> <Name> # #<-factor-> <Name> <Name> # #***  

MASS-LINK 12  

PERLND PWATER SURO 0.083333 COPY INPUT MEAN
END MASS-LINK 12

MASS-LINK 13
PERLND PWATER IFWO 0.083333 COPY INPUT MEAN
END MASS-LINK 13

END MASS-LINK

END RUN

```

Mitigated UCI File

```
RUN

GLOBAL
  WWHM4 model simulation
  START      1955 10 01      END      2008 09 30
  RUN INTERP OUTPUT LEVEL    3      0
  RESUME     0 RUN      1
  UNIT SYSTEM      1
END GLOBAL

FILES
<File> <Un#> <-----File Name----->***  

<-ID->
WDM      26  114.004 Twin Transit.wdm
MESSU    25  Mit114.004 Twin Transit.MES
        27  Mit114.004 Twin Transit.L61
        28  Mit114.004 Twin Transit.L62
        30  POC114.004 Twin Transit1.dat
END FILES

OPN SEQUENCE
  INGRP          INDELT 00:15
    PERLND      16
    IMPLND      11
    RCHRES      1
    COPY         1
    COPY        501
    DISPLAY      1
  END INGRP
END OPN SEQUENCE
DISPLAY
  DISPLAY-INFO1
    # - #<-----Title----->***TRAN PIVL DIG1 FIL1 PYR DIG2 FIL2 YRND
    1           Trapezoidal Pond 1           MAX             1   2   30   9
  END DISPLAY-INFO1
END DISPLAY
COPY
  TIMESERIES
    # - # NPT NMN ***
    1           1   1
    501         1   1
  END TIMESERIES
END COPY
GENER
  OPCODE
    # # OPCD ***
  END OPCODE
  PARM
    # # K ***
  END PARM
END GENER
PERLND
  GEN-INFO
    <PLS ><-----Name----->NBLKS  Unit-systems  Printer ***
    # - #                   User  t-series Engl Metr ***
                                in   out
    16  C, Lawn, Flat       1     1     1   27   0
  END GEN-INFO
  *** Section PWATER***

ACTIVITY
  <PLS > ***** Active Sections *****
  # - # ATMP SNOW PWAT SED PST PWG PQAL MSTL PEST NITR PHOS TRAC ***
  16      0     0     1     0     0     0     0     0     0     0     0     0
END ACTIVITY

PRINT-INFO
  <PLS > ***** Print-flags *****
  # - # ATMP SNOW PWAT SED PST PWG PQAL MSTL PEST NITR PHOS TRAC *****

```

```

16      0   0   4   0   0   0   0   0   0   0   0   0   0   0   1   9
END PRINT-INFO

PWAT-PARM1
<PLS > PWATER variable monthly parameter value flags ***
# - # CSNO RTOP UZFG VCS VUZ VNN VIFW VIRC VLE INF C HWT ***
16      0   0   0   0   0   0   0   0   0   0   0   0   0   0
END PWAT-PARM1

PWAT-PARM2
<PLS > PWATER input info: Part 2 ***
# - # ***FOREST LZSN INFILT LSUR SLSUR KVARY AGWRC
16      0       4.5     0.03    400    0.05    0.5    0.996
END PWAT-PARM2

PWAT-PARM3
<PLS > PWATER input info: Part 3 ***
# - # ***PETMAX PETMIN INFEXP INFILD DEEPFR BASETP AGWETP
16      0       0       2        2        0        0        0
END PWAT-PARM3

PWAT-PARM4
<PLS > PWATER input info: Part 4 ***
# - # CEPSC UZSN NSUR INTFW IRC LZETP ***
16      0.1     0.25    0.25      6      0.5    0.25
END PWAT-PARM4

PWAT-STATE1
<PLS > *** Initial conditions at start of simulation
         ran from 1990 to end of 1992 (pat 1-11-95) RUN 21 ***
# - # *** CEPS SURS UZS IFWS LZS AGWS GWVS
16      0       0       0       0     2.5     1       0
END PWAT-STATE1

END PERLND

IMPLND
GEN-INFO
<PLS ><-----Name-----> Unit-systems Printer ***
# - # User t-series Engl Metr ***
          in out ***
11      PARKING/FLAT      1   1   1   27   0
END GEN-INFO
*** Section IWATER***

ACTIVITY
<PLS > ***** Active Sections *****
# - # ATMP SNOW IWAT SLD IWG IQAL ***
11      0   0   1   0   0   0
END ACTIVITY

PRINT-INFO
<ILS > ***** Print-flags ***** PIVL PYR
# - # ATMP SNOW IWAT SLD IWG IQAL *****
11      0   0   4   0   0   0   1   9
END PRINT-INFO

IWAT-PARM1
<PLS > IWATER variable monthly parameter value flags ***
# - # CSNO RTOP VRS VNN RTL I *** 
11      0   0   0   0   0
END IWAT-PARM1

IWAT-PARM2
<PLS > IWATER input info: Part 2 ***
# - # *** LSUR SLSUR NSUR RETSC
11      400     0.01     0.1     0.1
END IWAT-PARM2

IWAT-PARM3
<PLS > IWATER input info: Part 3 ***

```

```

# - # ***PETMAX      PETMIN
11          0          0
END IWAT-PARM3

IWAT-STATE1
<PLS > *** Initial conditions at start of simulation
# - # *** RETS      SURS
11          0          0
END IWAT-STATE1

END IMPLND

SCHEMATIC
<-Source->           <-Area-->       <-Target->     MBLK   ***
<Name>   #             <-factor->      <Name>   #     Tbl#   ***
Basin    1***          PERLND   16          0.67    RCHRES   1     2
PERLND   16          0.67    RCHRES   1     3
IMPLND   11          1.27    RCHRES   1     5

*****Routing*****
PERLND   16          0.67    COPY     1     12
IMPLND   11          1.27    COPY     1     15
PERLND   16          0.67    COPY     1     13
RCHRES   1            1       COPY    501    16
END SCHEMATIC

NETWORK
<-Volume-> <-Grp> <-Member-><-Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name>   #           <Name> # #<-factor->strg <Name>   #   #     <Name> # #   ***
COPY     501 OUTPUT MEAN   1 1   48.4        DISPLAY  1       INPUT   TIMSER 1

<-Volume-> <-Grp> <-Member-><-Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name>   #           <Name> # #<-factor->strg <Name>   #   #     <Name> # #   ***
END NETWORK

RCHRES
GEN-INFO
  RCHRES      Name       Nexits   Unit Systems   Printer
  # - #-----><----> User T-series   Engl Metr LKFG
                           in   out
  1      Trapezoidal Pond-012   1     1     1     28     0     1
END GEN-INFO
*** Section RCHRES***

ACTIVITY
<PLS > ***** Active Sections *****
# - # HYFG ADFG CNFG HTFG SDFG GQFG OXFG NUFG PKFG PHFG ***
  1       1   0   0   0   0   0   0   0   0   0   0   0
END ACTIVITY

PRINT-INFO
<PLS > ***** Print-flags *****
# - # HYDR ADCA CONS HEAT   SED   GQL   OXRX   NUTR   PLNK   PHCB   PIVL   PYR
  1       4   0   0   0   0   0   0   0   0   0   0   1   9
END PRINT-INFO

HYDR-PARM1
RCHRES Flags for each HYDR Section
# - # VC A1 A2 A3 ODFVFG for each *** ODGTFG for each
  FG FG FG FG possible exit *** possible exit
  * * * * * * * * * * * * * * * *
  1       0   1   0   0   4   0   0   0   0   0   0   0   2   2   2   2   2
END HYDR-PARM1

HYDR-PARM2
# - # FTABNO      LEN      DELTH      STCOR      KS      DB50
<----><----><----><----><----><----><---->
***
```

```

1           1       0.01       0.0       0.0       0.5       0.0
END HYDR-PARM2
HYDR-INIT
  RCHRES Initial conditions for each HYDR section      ***
  # - # *** VOL   Initial value of COLIND    Initial value of OUTDGT
  *** ac-ft      for each possible exit   for each possible exit
<----><----> <----><----><----><----> *** <----><----><----><----><---->
  1           0       4.0  0.0  0.0  0.0  0.0       0.0  0.0  0.0  0.0  0.0
END HYDR-INIT
END RCHRES

SPEC-ACTIONS
END SPEC-ACTIONS
FTABLES
  FTABLE        1
  91     4
    Depth      Area      Volume  Outflow1 Velocity  Travel Time***  

    (ft)      (acres) (acre-ft)   (cfs)   (ft/sec)   (Minutes)***  

  0.000000  0.132599  0.000000  0.000000  

  0.055556  0.133764  0.007399  0.004396  

  0.111111  0.134935  0.014863  0.006217  

  0.166667  0.136111  0.022392  0.007614  

  0.222222  0.137292  0.029986  0.008791  

  0.277778  0.138478  0.037647  0.009829  

  0.333333  0.139669  0.045373  0.010767  

  0.388889  0.140866  0.053166  0.011630  

  0.444444  0.142067  0.061025  0.012433  

  0.500000  0.143274  0.068951  0.013187  

  0.555556  0.144485  0.076944  0.013901  

  0.611111  0.145702  0.085005  0.014579  

  0.666667  0.146924  0.093134  0.015227  

  0.722222  0.148151  0.101330  0.015849  

  0.777778  0.149383  0.109595  0.016447  

  0.833333  0.150620  0.117928  0.017025  

  0.888889  0.151862  0.126331  0.017583  

  0.944444  0.153109  0.134802  0.018124  

  1.000000  0.154362  0.143343  0.018650  

  1.055556  0.155619  0.151954  0.019161  

  1.111111  0.156882  0.160634  0.019658  

  1.166667  0.158150  0.169385  0.020144  

  1.222222  0.159423  0.178206  0.020618  

  1.277778  0.160700  0.187099  0.021081  

  1.333333  0.161983  0.196062  0.021535  

  1.388889  0.163272  0.205097  0.021979  

  1.444444  0.164565  0.214204  0.022414  

  1.500000  0.165863  0.223382  0.022841  

  1.555556  0.167167  0.232633  0.023260  

  1.611111  0.168475  0.241956  0.023672  

  1.666667  0.169789  0.251353  0.024076  

  1.722222  0.171108  0.260822  0.024474  

  1.777778  0.172431  0.270365  0.024866  

  1.833333  0.173760  0.279981  0.025252  

  1.888889  0.175094  0.289672  0.025631  

  1.944444  0.176434  0.299436  0.026006  

  2.000000  0.177778  0.309275  0.026374  

  2.055556  0.179127  0.319189  0.026738  

  2.111111  0.180482  0.329179  0.027097  

  2.166667  0.181841  0.339243  0.027451  

  2.222222  0.183206  0.349383  0.027801  

  2.277778  0.184576  0.359599  0.028146  

  2.333333  0.185950  0.369892  0.028488  

  2.388889  0.187330  0.380261  0.028825  

  2.444444  0.188715  0.390706  0.029158  

  2.500000  0.190106  0.401229  0.029487  

  2.555556  0.191501  0.411829  0.029813  

  2.611111  0.192901  0.422507  0.030136  

  2.666667  0.194307  0.433263  0.030455  

  2.722222  0.195717  0.444097  0.030770  

  2.777778  0.197133  0.455010  0.031098  

  2.833333  0.198554  0.466001  0.032724

```

2.888889	0.199980	0.477071	0.035279
2.944444	0.201411	0.488221	0.038418
3.000000	0.202847	0.499450	0.042002
3.055556	0.204288	0.510760	0.045944
3.111111	0.205734	0.522149	0.050183
3.166667	0.207185	0.533619	0.054672
3.222222	0.208642	0.545170	0.059372
3.277778	0.210104	0.556802	0.064252
3.333333	0.211570	0.568515	0.069283
3.388889	0.213042	0.580310	0.074443
3.444444	0.214519	0.592186	0.079708
3.500000	0.216001	0.604145	0.085060
3.555556	0.217488	0.616187	0.090481
3.611111	0.218980	0.628311	0.095955
3.666667	0.220478	0.640518	0.101466
3.722222	0.221980	0.652808	0.107000
3.777778	0.223487	0.665182	0.112602
3.833333	0.225000	0.677640	0.119298
3.888889	0.226518	0.690183	0.126164
3.944444	0.228041	0.702809	0.133194
4.000000	0.229568	0.715521	0.140385
4.055556	0.231101	0.728317	0.348914
4.111111	0.232640	0.741199	0.728704
4.166667	0.234183	0.754166	1.215423
4.222222	0.235731	0.767219	1.778352
4.277778	0.237284	0.780358	2.390495
4.333333	0.238843	0.793584	3.024427
4.388889	0.240407	0.806897	3.652076
4.444444	0.241975	0.820296	4.246035
4.500000	0.243549	0.833783	4.781739
4.555556	0.245128	0.847357	5.240244
4.611111	0.246712	0.861019	5.611474
4.666667	0.248301	0.874770	5.897868
4.722222	0.249895	0.888609	6.118372
4.777778	0.251495	0.902536	6.393703
4.833333	0.253099	0.916553	6.613299
4.888889	0.254709	0.930658	6.825696
4.944444	0.256323	0.944854	7.031558
5.000000	0.257943	0.959139	7.231455

END FTABLE 1

END FTABLES

EXT SOURCES

<-Volume-> <Member> SsysSgap<--Mult-->Tran		<-Target vols>		<-Grp> <-Member-> ***	
<Name>	#	<Name>	#	<Name>	# # ***
WDM	2	PREC	ENGL	0.8	PERLND 1 999 EXTNL PREC
WDM	2	PREC	ENGL	0.8	IMPLND 1 999 EXTNL PREC
WDM	1	EVAP	ENGL	0.76	PERLND 1 999 EXTNL PETINP
WDM	1	EVAP	ENGL	0.76	IMPLND 1 999 EXTNL PETINP

END EXT SOURCES

EXT TARGETS

<-Volume-> <-Grp> <-Member-><--Mult-->Tran		<-Volume-> <Member> Tsys Tgap Amd ***					
<Name>	#	<Name>	# #<-factor->strg	<Name>	#	<Name>	tem strg strg***
RCHRES	1	HYDR RO	1 1	1	WDM	1000	FLOW ENGL REPL
RCHRES	1	HYDR STAGE	1 1	1	WDM	1001	STAG ENGL REPL
COPY	1	OUTPUT MEAN	1 1	48.4	WDM	701	FLOW ENGL REPL
COPY	501	OUTPUT MEAN	1 1	48.4	WDM	801	FLOW ENGL REPL

END EXT TARGETS

MASS-LINK

<Volume>	<-Grp>	<-Member-><--Mult-->	<Target>	<-Grp> <-Member->***	
<Name>		<Name> # #<-factor->	<Name>	<Name> # #***	
PERLND	PWATER	SURO	0.083333	RCHRES	INFLOW IVOL
PERLND	PWATER	IFWO	0.083333	RCHRES	INFLOW IVOL

MASS-LINK 3
PERLND PWATER IFWO 0.083333

```
END MASS-LINK      3

MASS-LINK          5
IMPLND    IWATER  SURO      0.083333   RCHRES      INFLOW  IVOL
END MASS-LINK      5

MASS-LINK          12
PERLND    PWATER  SURO      0.083333   COPY        INPUT   MEAN
END MASS-LINK      12

MASS-LINK          13
PERLND    PWATER  IFWO      0.083333   COPY        INPUT   MEAN
END MASS-LINK      13

MASS-LINK          15
IMPLND    IWATER  SURO      0.083333   COPY        INPUT   MEAN
END MASS-LINK      15

MASS-LINK          16
RCHRES    ROFLOW
END MASS-LINK      16
```

END MASS-LINK

END RUN

Predeveloped HSPF Message File

Mitigated HSPF Message File

Disclaimer

Legal Notice

This program and accompanying documentation are provided 'as-is' without warranty of any kind. The entire risk regarding the performance and results of this program is assumed by End User. Clear Creek Solutions Inc. and the governmental licensee or sublicensees disclaim all warranties, either expressed or implied, including but not limited to implied warranties of program and accompanying documentation. In no event shall Clear Creek Solutions Inc. be liable for any damages whatsoever (including without limitation to damages for loss of business profits, loss of business information, business interruption, and the like) arising out of the use of, or inability to use this program even if Clear Creek Solutions Inc. or their authorized representatives have been advised of the possibility of such damages. Software Copyright © by : Clear Creek Solutions, Inc. 2005-2022; All Rights Reserved.

Clear Creek Solutions, Inc.
6200 Capitol Blvd. Ste F
Olympia, WA. 98501
Toll Free 1(866)943-0304
Local (360)943-0304

www.clearcreeksolutions.com


APPENDIX 5

PRELIMINARY PLANS

JSACIVIL

Engineering | Planning | Management

111 Tumwater Blvd SE, Suite C210 | Tumwater, WA 98501



GENERAL NOTES

1. SPOT ELEVATIONS REFER TO FINISHED GRADE AT FLOW LINE UNLESS OTHERWISE NOTED.
2. APPROXIMATE SPOT ELEVATIONS:
HP = HIGH POINT
LP = LOW POINT
EG = EXISTING GRADE
TBC = TOP OF BANK OR Curb
SK = SIGHTLINE
3. CROWN SLOPES TO EXISTING GRADE SHALL NOT EXCEED 1:1

SITE DATA

ADDRESS	1697 BISHOP ROAD
TPN	177500000
PARCEL SIZE	22.28 ACRES
JURISDICTION	CITY OF ODEMAIS - USA
ZONING	C-G & T-L

SCALE IN FEET

0 50 100 150 200

250 300 350 400

450 500 550 600

650 700 750 800

850 900 950 1000

1050 1100 1150 1200

1250 1300 1350 1400

1450 1500 1550 1600

1650 1700 1750 1800

1850 1900 1950 2000

2050 2100 2150 2200

2250 2300 2350 2400

2450 2500 2550 2600

2650 2700 2750 2800

2850 2900 2950 3000

3050 3100 3150 3200

3250 3300 3350 3400

3450 3500 3550 3600

3650 3700 3750 3800

3850 3900 3950 4000

4050 4100 4150 4200

4250 4300 4350 4400

4450 4500 4550 4600

4650 4700 4750 4800

4850 4900 4950 5000

5050 5100 5150 5200

5250 5300 5350 5400

5450 5500 5550 5600

5650 5700 5750 5800

5850 5900 5950 6000

6050 6100 6150 6200

6250 6300 6350 6400

6450 6500 6550 6600

6650 6700 6750 6800

6850 6900 6950 7000

7050 7100 7150 7200

7250 7300 7350 7400

7450 7500 7550 7600

7650 7700 7750 7800

7850 7900 7950 8000

8050 8100 8150 8200

8250 8300 8350 8400

8450 8500 8550 8600

8650 8700 8750 8800

8850 8900 8950 9000

9050 9100 9150 9200

9250 9300 9350 9400

9450 9500 9550 9600

9650 9700 9750 9800

9850 9900 9950 10000

10050 10100 10150 10200

10250 10300 10350 10400

10450 10500 10550 10600

10650 10700 10750 10800

10850 10900 10950 11000

11050 11100 11150 11200

11250 11300 11350 11400

11450 11500 11550 11600

11650 11700 11750 11800

11850 11900 11950 12000

12050 12100 12150 12200

12250 12300 12350 12400

12450 12500 12550 12600

12650 12700 12750 12800

12850 12900 12950 13000

13050 13100 13150 13200

13250 13300 13350 13400

13450 13500 13550 13600

13650 13700 13750 13800

13850 13900 13950 14000

14050 14100 14150 14200

14250 14300 14350 14400

14450 14500 14550 14600

14650 14700 14750 14800

14850 14900 14950 15000

15050 15100 15150 15200

15250 15300 15350 15400

15450 15500 15550 15600

15650 15700 15750 15800

15850 15900 15950 16000

16050 16100 16150 16200

16250 16300 16350 16400

16450 16500 16550 16600

16650 16700 16750 16800

16850 16900 16950 17000

17050 17100 17150 17200

17250 17300 17350 17400

17450 17500 17550 17600

17650 17700 17750 17800

17850 17900 17950 18000

18050 18100 18150 18200

18250 18300 18350 18400

18450 18500 18550 18600

18650 18700 18750 18800

18850 18900 18950 19000

19050 19100 19150 19200

19250 19300 19350 19400

19450 19500 19550 19600

19650 19700 19750 19800

19850 19900 19950 20000

20050 20100 20150 20200

20250 20300 20350 20400

20450 20500 20550 20600

20650 20700 20750 20800

20850 20900 20950 21000

21050 21100 21150 21200

21250 21300 21350 21400

21450 21500 21550 21600

21650 21700 21750 21800

21850 21900 21950 22000

22050 22100 22150 22200

22250 22300 22350 22400

22450 22500 22550 22600

22650 22700 22750 22800

22850 22900 22950 23000

23050 23100 23150 23200

23250 23300 23350 23400

23450 23500 23550 23600

23650 23700 23750 23800

23850 23900 23950 24000

24050 24100 24150 24200

24250 24300 24350 24400

24450 24500 24550 24600

24650 24700 24750 24800

24850 24900 24950 25000

25050 25100 25150 25200

25250 25300 25350 25400

25450 25500 25550 25600

25650 25700 25750 25800

25850 25900 25950 26000

26050 26100 26150 26200

26250 26300 26350 26400

26450 26500 26550 26600

26650 26700 26750 26800

26850 26900 26950 27000

27050 27100 27150 27200

27250 27300 27350 27400

27450 27500 27550 27600

27650 27700 27750 27800

27850 27900 27950 28000

28050 28100 28150 28200

28250 28300 28350 28400

28450 28500 28550 28600

28650 28700 28750 28800

28850 28900 28950 29000

29050 29100 29150 29200

29250 29300 29350 29400

29450 29500 29550 29600

29650 29700 29750 29800

29850 29900 29950 30000

30050 30100 30150 30200

30250 30300 30350 30400

30450 30500 30550 30600

30650 30700 30750 30800

30850 30900 30950 31000

31050 31100 31150 31200

31250 31300 31350 31400

31450 31500 31550 31600

31650 31700 31750 31800

31850 31900 31950 32000

32050 32100 32150 32200

32250 32300 32350 32400

32450 32500 32550 32600

32650 32700 32750 32800

32850 32900 32950 33000

33050 33100 33150 33200

33250 33300 33350 33400

33450 33500 33550 33600

33650 33700 33750 33800

33850 33900 33950 34000

34050 34100 34150 34200

34250 34300 34350 34400

34450 34500 34550 34600

34650 34700 34750 34800

34850 34900 34950 35000

35050 35100 35150 35200

35250 35300 35350 35400

35450 35500 35550 35600

35650 35700 35750 35800

35850 35900 35950 36000

36050 36100 36150 36200

36250 36300 36350 36400

36450 36500 36550 36600

36650 36700 36750 36800



36850 36900 36950 37000


37050 37100 37150 37200

37250 37300 37350 37400

37450 37500 37550 37600

37650 37700 377





LEGEND


VICINITY MAP (INTS)



Engineering | Planning | Management

JSA CIVI

The logo for Twin Transit features a stylized 'T' and 'I' in blue and red, with the word 'Twin' above 'Transit' and 'GOING YOUR WAY' below it. To the right is a scale bar with a diamond at the top, labeled 'SCALE' and '0 30 60 FEET'. The word 'PRELIMINARY' is written diagonally across the bottom right.




SITE DATA

REC. DA/F.	COMMENT	BY
0	09/29/22	ISSUED FOR REVIEW
		EJL

DRAWN BY:	L. SAYER
CHECKED BY:	B. JOHNSON

PRELIMINARY



SCALE IN FEET